

## KVM Switch - 4-Port Desktop KVM Switch (USB)

MODEL NUMBER: **B006-004-R**



### Description

Tripp Lite's 4-port Desktop USB KVM Switch is the optimal solution for controlling up to 4 USB computers from one keyboard, mouse, and monitor. It features keyboard and mouse emulation for error-free boot-ups and works on all operating systems. This device also supports 180MHz video resolutions up to 1920 x 1440 pixels without any noticeable degradation. It features a compact design that does not require external power, software, or complicated set-up procedures.

### Features

- Control up to 4 USB computers from a single keyboard, mouse and monitor
- Console Ports: HD15 Female (Monitor) and 2 USB A Female (Keyboard/Mouse)
- Computer Ports: 4 HD15 Male (Monitor) and 4 USB B Female (Dual Keyboard/Mouse)
- Includes 2 USB A Female ports for sharing of USB peripherals between connected computers
- 2 LEDs per port; one indicates when the computer is connected & on, the other indicates when the computer has been selected
- Supports 180MHz video resolutions up to 1920 x 1440
- Supports VGA, SVGA, or Multisync monitors
- Does not require external power, software, or complicated set-up procedures
- Select a computer via front panel push-buttons
- Includes autoscan feature
- Keyboard and mouse emulation for dependable computer boot-up
- Compatible with all operating systems
- Compatible with most mice; including scroll mice

### Highlights

- USB Connections on both Console and Server side
- P758-Series KVM Cable kit required to connect to a computer
- Push Button switching on the front of the unit
- Built-in 2-Port USB hub shares two USB peripherals between attached systems
- OS independent operation - use with PCs or MACs

### Package Includes

- B006-004-R 4-port USB KVM Switch
- Instruction manual with warranty information

## Specifications

### OVERVIEW



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

UPC Code	037332014962
Users	1
Console	No
Max CPU	4
Product Rear View	B006-004-R-rear.pdf
<b>PHYSICAL</b>	
Shipping Dimensions (hwd / in.)	4.000 x 13.000 x 8.500
Shipping Dimensions (hwd / cm)	10.16 x 33.02 x 21.59
Shipping Weight (lbs.)	3.5000
Shipping Weight (kg)	1.59
Unit Weight (lbs.)	3
Unit Weight (kg)	1.36
LCD Monitor (in.)	Not Applicable
LCD Monitor (cm)	Not Applicable
<b>ENVIRONMENTAL</b>	
BTUs	50Hz, 2.7 / 60Hz, 2.4
<b>COMMUNICATIONS</b>	
Port Control	Push Buttons
IP Remote Access	No
<b>CONNECTIONS</b>	
Ports	4
Computer/Server Ports - Port 1	HD15 (Male)
Computer/Server Ports - Port 2	USB B (Female)
PC/Server Connections	USB

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>