



P/N	MATERIAL	FLAMMABILITY RATING TEST METHOD IEC 60695-2-11
94544-7008	PA 6.6 NATURAL	IEC 60335 - 1 REV. 4 GWT 750 °C

IMBALLO: BOX CON SACCHETTO DI NYLON  
PACKAGING: BOX WITH PLASTIC BAG

Std.Descr.: HOUSING DUAL ROW WITH LOCK 8 CKT\*

S.P.Q.: 800 pz.

IEC NO: Z2009-0066 DRWN: L.SANTESO08/12/02 CHKD: L.SANTESO08/12/05 APPR: GZUIN 2008/12/05	DESCRIPTION REV B2	QUALITY SYMBOLS ▽ - 0 ▽ - 0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH	SCALE 2:1 DESIGN UNITS METRIC DIMENSION STYLE MM ONLY	FIRST ANGLE PROJECTION REVISE ON CAD ONLY
		4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± 0.10 ± --- 1 PLACE ± 0.2 ± ---	DRAWN BY FGOTTARD DATE 2001-12-20	TITLE HOUSING 8 CKT DOPPIA FILA CON S.LOCK E AGGANCIO	
		ANGULAR ± 2 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	CHECKED BY MTESTAGU DATE 2001-12-20	MOLEX MOLEX INCORPORATED	
		APPROVED BY GZUIN DATE 2001-12-20	MATERIAL NO. 94544-7008 DOCUMENT NO. SD-94544-001 SHEET NO. 1 OF 1	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	