




M300 Connectors

Male Cable Connector Contacts

- Crimp barrel meets all crimp guidelines and standards.
- 10A current capacity, resists high vibration and shock.
- Withstands extremes of temperature: -65°C to +175°C.



M300

CONTACTS	WIRE STRIPPING DETAILS										
<p>18-20 AWG</p>  <p>22 AWG</p> 	 <p>18-20 AWG - 0.180 max 22 AWG - 0.140 max</p> <p>2.00 nominal</p>										
<h3>TOOLS</h3>											
<p>Recommended Crimp Tool - M22520/2-01 Positioner - Z80-058 Contact Insertion/Removal Tool - Z300-902</p>	<ul style="list-style-type: none"> ➤ Male crimp housings shown on previous page. ➤ Instruction sheets available at www.harwin.com/instructions. 										
<h3>HOW TO ORDER</h3>											
<p style="text-align: center;">M300 - 10X 00 45</p> <div style="display: flex; justify-content: space-between;"> <div data-bbox="147 1627 337 1669" style="border: 1px solid black; padding: 2px;"> <p>SERIES CODE</p> </div> <div data-bbox="147 1696 479 1816" style="border: 1px solid black; padding: 2px;"> <table border="1"> <thead> <tr> <th colspan="2">TYPE</th> </tr> </thead> <tbody> <tr> <td>101</td> <td>18-20 AWG crimp contact</td> </tr> <tr> <td>102</td> <td>22 AWG crimp contact</td> </tr> </tbody> </table> </div> <div data-bbox="1323 1680 1474 1764" style="border: 1px solid black; padding: 2px;"> <table border="1"> <thead> <tr> <th colspan="2">FINISH</th> </tr> </thead> <tbody> <tr> <td>45</td> <td>Gold</td> </tr> </tbody> </table> </div> </div>		TYPE		101	18-20 AWG crimp contact	102	22 AWG crimp contact	FINISH		45	Gold
TYPE											
101	18-20 AWG crimp contact										
102	22 AWG crimp contact										
FINISH											
45	Gold										

All dimensions in mm.